

LIVING



AC4 / 32



THICKNESS: 8MM
BOARD SIZE: 1383x193x8mm
BOX QUANTITY: 9 panels / 2.4m²
USE CLASS: 32 / AC4



BEFORE YOU START

- **Consult instructions for details on site conditions.**
 - Moisture content of cement subfloor must be ≤ 3% on a Tramex Concrete Encounter (2.0% C.M. Method).
 - Liquid/Anhydrite screeds must be ≤ 0.3% C.M.
 - Wood subfloor moisture should be 10% +/-2%
- Install 500 gauge polythene on all concrete surfaces. Overlap joints by 200mm and seal with duck tape.
- Check that the subfloor is level and even before installation – max. 3mm differential over 1mt.
- Flooring Underlay: We recommend that all floors are installed over a good quality underlay with a maximum thickness of 3mm. Do not use underlays over 3mm as per manufacturers guidelines.
- Not suitable for use in wet rooms.
- LEAVE BOXES UNOPENED IN ROOM FOR 48 HOURS PRIOR TO INSTALLATION.
- Floors need to be swept/vacuumed fully before installation commences, dirt/grit underneath will cause the product to under perform.
- Please see fitting instructions overleaf.

DURING & AFTER INSTALLATION

- Please inspect all boards in good light for any visible faults or defects prior to installation. No claims are accepted once boards are installed.
- Select board direction e.g. towards light or longest room dimension. This floor has a click system.
- Expansion gap of 12mm must be provided at all doorways, around perimeter and all fixed objects - see reverse for guidelines and details. For large individual rooms, there are limits to the size of an area possible without an expansion break. Details overleaf.
- Do not place heavy objects or units directly on top of the laminate flooring e.g. kitchens, island units, built-in wardrobes. These must be installed first and then leave the required 12mm expansion gap at the carcass leg.
- Follow installation instructions for first and second row.
- Stagger joints by min. 650mm thereafter.
- Select finishing profiles, skirting, pipe covers, doorway slips.
- Use felt pads and protective castors underneath furniture legs. Please use suitable cleaning products for aftercare.
- **Do not use steam cleaners on Laminate Flooring.**



Easy Push Down
Drop Lock System

30 YEAR RESIDENTIAL WARRANTY
as per manufacturer's terms

